

# PRODUCT SHEET

## WOODCRACKER W-SERIES

|   | W 600   | W 820   | W 1000  | W 1350  | W 1800  |
|---|---------|---------|---------|---------|---------|
| Tongs opening (mm)                        | 620     | 820     | 1040    | 1370    | 1830    |
| Splitting force at 240 bar (t)            | 26      | 26      | 26      | 34      | 47 ***  |
| Weight (kg)                               | 310     | 370     | 580     | 990     | 1990    |
| Recommended pump flow capacity * (l/min.) | 25-60   | 25-60   | 40-80   | 80-150  | 100-190 |
| Recommended operating pressure * (bar)    | 190-250 | 190-250 | 190-250 | 220-270 | 240-300 |
| Service weight carrier vehicle ** (t)     | 6       | 10      | 14      | 20      | 30      |
| Roller system                             | ●       | ●       | —       | —       | —       |
| Optional: Autospeed                       | ●       | ●       | ●       | —       | —       |
| Optional: Rotator                         | ●       | ●       | ●       | ●       | ●       |

● available | — not available

\* Depending on the operating mode or equipment of the wood cracker

\*\* Depending on the equipment of the carrier vehicle

Technical data is non-binding.  
Subject to change for reasons of further development.

