

PRODUCT SHEET

WOODCRACKER C-SERIES

	C 250	C 350	C 450	C 550
Cutting diametre soft wood (mm)	330	400	500	600
Cutting diametre hard wood (mm)	280	350	450	550
Gripper opening (mm)	930	1430	1600	1600
Diametre of shears (mm)	450	700	800	900
Weight (Base – Full equipment) (kg)	580-970	1150-1620	1760-2350	2000-2620
Recommended pump flow capacity * (l/min.)	50-100	70-150	80-160	100-190
Recommended pump flow capacity (optional functions) * (l/min.)	35-50	45-60	45-60	50-70
Recommended operating pressure (bar)	280	280	280	280
Service weight carrier vehicle ** (t)	7-15	14-20	20-25	24-30
Multigrip	integriert	integriert	integriert	integriert
Optional: Autospeed	●	●	●	●
Optional: Cylinder swivel mechanism	● 2 x 48°	● 2 x 48°	● 2 x 48°	● 2 x 48°
Optional: Tiltator	●	●	●	●
Optional: Power-Tiltator	—	●	●	●
Optional: Automatic lubrication system for Tiltator	●	●	●	●
Optional: Accumulator	●	● mit Schnellwechsler QC	● mit Schnellwechsler QC	● mit Schnellwechsler QC

● available | - not available

* Depending on the operating mode or equipment of the wood cracker

** Depending on the equipment of the carrier vehicle

Technical data is non-binding.
Subject to change for reasons of further development.

